



## Technical Data LIGHT COLLECTION

**Luxury, high performance PVC-floor covering for heavy duty residential application.**

Covering type in accordance with EN 649	Heterogeneous Plank Wood	Heterogeneous Tiles
Number of colours	38	27
Pack. Unit/Pallet	3,34 m <sup>2</sup> /240,48 m <sup>2</sup>	3,34 m <sup>2</sup> /240,48 m <sup>2</sup>
Performance classification EN 685	21-23, 31	21-23, 31
Total thickness EN 428	2,0 mm	2,0 mm
Wear layer thickness EN 429	0,3 mm	0,3 mm
Surface treatment	yes/PU	yes/PU
Bevelled edges	no	no
Total weight EN 430	3,8 kg/m <sup>2</sup>	3,8 kg/m <sup>2</sup>
Residual indentation EN 433	0,05 mm	0,05 mm
Castor chair suitability EN 425	suitable for castor chairs in acc. with DIN 68131, type W	suitable for castor chairs in acc. with DIN 68131, type W
Underfloor heating	suitable (up to 28°C)	suitable (up to 28°C)
Behaviour to fire EN 13501-1	Bfl-s1	Bfl-s1
Impact sound improvement EN 140-4	4dB	4dB
Colour fastness EN ISO 105-B02	> 6	> 6
Electrostatic characteristics EN 1081	> 10 <sup>10</sup>	> 10 <sup>10</sup>
Chemical resistance EN 423	conforms*	conforms*
Slip resistance	R9	R9
Adhesive recommendation	see installation instruction	see installation instruction
Maintenance/Cleaning recommendation	CC-Dr. Schutz	CC-Dr. Schutz

\*Vis-à-vis the short-term effects of normal, domestic agents.

**Please also note the installation and cleaning and care instructions.**

### PROJECT FLOORS GmbH

Kalscheurener Str. 19 • D-50354 Hürth  
 Telefon +49 (0) 2233 9687-0 • Fax +49 (0) 2233 9687-10  
 www.project-floors.com • info@project-floors.com